

## Vaisala HUMICAP® Humidity and Temperature Probe HMP110

Vaisala HUMICAP® Humidity and Temperature Probe		HMP110											PRICE
1 Output signals	0...1 V 0...2.5 V 0...5 V 1 ...5V Scaling for 4...20 mA converter (channel 1 only) RS485 Interface for Vaisala devices (VDIGI)	A B C D I R V											
2 Measured parameter for channel 1	RS485 RH T (-40 ... +80 °C) Td (-40 ... +80 °C)	0 1 5 6											
3 Measured parameter for channel 2	RS485 or current interface RH T (-40 ... +80 °C) Td (-40 ... +80 °C)	0 1 5 6											
4 Sensor protection	Plastic grid with filter Plastic grid Stainless steel sintered filter	A B C											
5 Accessories	No accessories Pair of plastic nuts Duct installation kit 215619	0 1 3											
6 Humidity sensor	<b>Humicap180R</b>									C			
7 Probe cable length	No cable 60 °C cable 0.3 m HMP50Z032 60 °C cable 3 m HMP50Z30A High temperature cable 1.5 m High temperature cable 3 m 180 °C FEP cable 3m 226902											1 2 3 4 5 F	
8 User guide	No user guide Multilingual quick guide											A B	
9 Loop power converter	No converter 4...20 mA loop power converter											0 1	
											TOTAL		
											QTY		
											TOTAL VALUE		

Selections in bold are included in the prices of the basic versions.  
Selections in italic are available at an extra price.

Example of order code with typical settings:

HMP110 A 1 5 A 0 C 1 B 0