

HMT130 Humidity and Temperature Transmitter

		1	2	3	4	5	6	7	8	9	10	11	12	13	14	Price	
Vaisala HUMICAP® Humidity and Temperature Transmitter		HMT130														0	
1	Output parameters	Humidity output only	H														
		Humidity and temperature output	K														
2	Transmitter type	Wall mount/fixed probe	A														
		Remote probe with 3 m cable	B														
		Remote probe with 5 m cable	C														
		Remote probe with 10 m cable	D														
		Remote probe with 10 m cable + 10 m extension	E														
3	Display	No display														0	
		Display														1	
4	Output signal	0...1 V														B	
		3-wire														C	
		0...5 V														D	
		3-wire														X	
	SPECIAL	0...10 V														D	
		Define scale: 3-wire _____ V *)														X	
5	Parameter for Output 1	RH														1	
		0...100 %RH														2	
		Tdf														3	
		-20...+80 °C (-4...+176 °F)														4	
		H														X	
		-40...+1500 kJ/h (-9.5...+652.6 Btu/lb)															
		Tw															
		0...+80 °C (+32...+176 °F)															
	SPECIAL	Define quantity _____ Scale _____														X	
6	Parameter for Output 2	None														A	
		T														B	
		-40...+60 °C (-40...+140 °F)														C	
		-20...+80 °C (-4...+176 °F)														D	
		0...+60 °C (+32...+140 °F)														E	
		-40...+80 °C (-40...+176 °F)														F	
		0...+50 °C (+32...+122 °F)														X	
	SPECIAL	Define scale _____														X	
7																0	
8	Display Units	Metric														1	
		Non metric														2	
9	Sensor protection	Plastic grid														1	
		Plastic grid with PTFE filter														2	
		Stainless steel sintered filter (for remote probes only)														3	
10	Transmitter installation	No accessories														A	
		Rainshield with installation kit (215109)														C	
11	Installation kit for probe	No accessories														1	
		Duct installation kit (215619)														2	
		Probe mounting flange (226061)														3	
		Outdoor installation: DTR504A Radiation Shield with probe installation kit (DTR504A)														5	
12	Cable bushings	Cable gland for 2...6 mm diameter cable														A	
		Conduit fitting PG9														B	
		Conduit fitting NPT 1/2"														C	
		No bushing (rubber plug)														D	
		All bushings (includes A, B, C and D)														Z	
13	PC Accessories	No														0	
		Service cable for PC, USB (219685)														1	
14	Operation manual	No manual														A	
		Multilingual														Z	

*) Voltage output value between 0...10 V

Total
QTY
Total value

Selections in bold are included in the prices of the basic versions
Selections in italic are available at an extra cost

Example of order code with typical settings

HMT130	K	A	1	D	1	B	0	1	1	A	1	A	0	Z
--------	---	---	---	---	---	---	---	---	---	---	---	---	---	---